

GIGABIT ETHERNET FIBER MEDIA CONVERTER POE



INTEGRATED POWER & DATA TRANSMISSION:

Provides both power and data transmission via Cat cables, with PoE ports supplying power in line with IEEE802.3af/at standards. Auto-sensing function ensures power is only supplied to compatible devices.



VERSATILE APPLICATION:

Ideal for powering and connecting wireless access points (AP) and IP-based surveillance network solutions, making it a cost-effective choice for various network setups.



RELIABLE & INTELLIGENT DESIGN:

Features automatic identification of PoE supply voltage, power, speed, duplex mode, and cable type. If a PoE device is disconnected, power supply ceases, ensuring safety and efficiency.



COMPREHENSIVE FEATURES & INDICATORS:

Supports a range of IEEE standards, including flow control for both full and half-duplex modes. LED indicators provide real-time monitoring of power, link, activity, and speed, ensuring smooth operations.

SPECIFICATION



PoE Port	2 POE 10/100/1000Mbps
Uplink	UTP 10/100/1000Mbps,Fiber 1000Mbps
Bandwidth	1Gbps
Address Database Size	4K
Power Supply	DC52V
Max.Power Per Port	15.4W(IEEE802.3af) default,25.5W(IEEE802.3at) optional
Network Protocols	IEEE 802.3i 10BASET; IEEE 802.3u 100BASETX;IEEE 802.3x Flow Control; IEEE 802.laf/at DTE Power via MDI; IEEE 802.3af/at IEEE 802.3ab 1000BASE-T
LED Display	Power,POE, Ethernet
Distance	100meter for UTP ports;0~20km for Fiber ports
Fiber Specification	Fiber Port: SC(SC/UPC, SC/APC, but SC/UPC is recommended), Wavelength/Distance: Single Fiber 1310nm/1550nm(20km)

APPLICATION

- Wireless Access Point
- IP Camera
- IP Phone
- Computer Networks

Elfcam has made all efforts to ensure the accuracy of the information, but all information in this document does not constitute any kind of warranty.



No. 1 supplier of fiber optic materials



(France) B4, 32 Avenue d'épi d'or, 94800, Villejuif

(Deutschland) Kölner Str. 366, 40227 Düsseldorf



Phone: +33 07 49 95 50 99



Email: contact@elfcams.com



www.elfcams.com